



PRODUCT DATA SHEET

GEAR OIL 75W90

Gear Oil

GL5

GEAR OIL 75W90 is a multigrade lubricant containing sophisticated extreme pressure additives designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions.

SPECIFICATIONS

GEAR OIL 75W90 meets or exceeds the following specifications.

- API GL5
- MACK GO - J PLUS
- SAE J2360
- SAE 75W90
- API MT-1

APPLICATIONS

GEAR OIL 75W90 is recommended for use in manual transaxles incorporating hypoid gears and manual transaxles fitted to selected late model European passenger cars.

GEAR OIL 75W90 can be used where gear shift problems are encountered to allow for easier gear operation.

GEAR OIL 75W90 will provide maximum protection when subjected to severe shock loads, exceptional oxidation stability during high ambient temperatures, outstanding corrosion protection and anti-foam additives protect gear box and differential components.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	75W90
Specific gravity at 15 c	0.869
Viscosity at 40c, mm ² /s (cSt)	100
Viscosity 100c, mm ² /s (cSt)	15
Viscosity index	157
Flash Point C	227

PACKAGE SIZE 4, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.