



PRODUCT DATA SHEET

SUPER HT (Bentone) Grease

NLGI 2

SUPER HT (Bentone) GREASE is a bentone clay multi use lubricating grease for bearing applications where temperatures are very high or below freezing.

SPECIFICATIONS

SUPER HT (Bentone) GREASE meets or exceeds the following specifications.

- NLGI 2

APPLICATIONS

SUPER HT (Bentone) GREASE is a prime recommendation for automotive, marine and industrial bearings offering long service life and fortified with effective oxidation, rust and corrosion inhibitors.

SUPER HT (Bentone) GREASE does not have a melting point and the low temperature properties ensure suitability for applications where temperatures are below freezing.

SUPER HT (Bentone) GREASE is water resistant with outstanding resistance to water washout so that lubrication is sustained under water contaminating environments.

SUPER HT (Bentone) GREASE is shear resistant maintaining consistency as it does not thin out under high shear where other greases may thin out and cause premature wear or equipment failure.

SUPER HT (Bentone) GREASE has excellent pump ability characteristics over wide temperature range and minimises oxidation in very high temperature applications thereby promoting longer service life in these hostile environments.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	NLGI 2
After 60 strokes	270
After 10,000 strokes	288
Dropping Point deg C	Does Not Melt
Water Washout @ 80 deg C %	0
Wheel Bearing Leakage gm	0.78
Timken OK Load Kg	30
Appearance	Amber

PACKAGE SIZE 450 Gm

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.